

BELT DRESSING



The Belt Dressing without any harmful chlorinated solvents.

- Prevents belt slippage on flat, round and V-belts
- Extends belt life and pulling bearing life
- Does not contain chlorinated solvents that deteriorate drive belts
- Eliminates squeaks from slipping belts
- Colorless
- Can be used in wet outdoor conditions
- Low odor
- NSF registration category H1 - #134508

Belt Dressing is available in this size:

10 oz. (284 grams) aerosol Part No. 02216

Typical applications where Belt Dressing can be used:

- | | |
|---------------|-------------------------|
| ● Bushings | ● Sanding Belts |
| ● Flat Belts | ● Appliance Drive Belts |
| ● Round Belts | ● Polishing Belts |
| ● Bearings | ● Toothed Belts |
| ● V-Belts | |

General Information

Formulated to be non-drying, water resistant and chemically stable, Belt Dressing extends the life of drive belts by improving traction and allowing runs under reduced belt tension.

Material Safety Data Sheets are available upon request.

Properties (Residual Film)

Flash point:
(PMCC, ASTM D 93):
320°F

Appearance:
Clear, Colorless

Viscosity @ 210°F:
(635-690 cSt)
3000 SUS



LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.

TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2005 LPS Laboratories • All Rights Reserved • Rev. 01/2005 • Form #X2216