



CHAIN LUBRICANT

FOOD GRADE



FEATURES

- Excellent for applications involving incidental food contact on food processing equipment
- Does not contain silicone
- NSF® registered HI # 132899
- Foaming action provides extra penetration & lubrication
- Oily, wet film extends chain life
- Reduces friction & wear



Registration No. 132899
Category Code HI

APPLICATIONS

- Bottling Equipment
- Bushings
- Casters
- Chains
- Channels
- Conveyors
- Drives
- Filling Equipment
- Food Processing Equipment
- Food Service Carts
- Food Racks
- Machines
- Pins
- Rollers
- Sliding Tracks



PROPERTIES

Appearance/Physical State:
Liquid

ASTM D 2266 4-Ball Wear Scar
Diameter (40 kg. load):
.50 mm

Base Oil Viscosity:
@ 100°F, SUS 205
@ 40°C, cST 39.9

Boiling/Condensation Point:
N.E.

Color:
Clear

Odor:

Mild

Temperature Range:

20°F – 325°F (7°C – 163°C)

Specific Gravity (water=1):

0.857 – 0.867 @ 77°F (25°C)

Vapor Density (air=1):

>1

VOC Content:

15% – 123 g/l – 1.03 lbs. /gal.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

PACKAGE

Net Fill
12 oz. (340 grams) aerosol

Part No.
06016

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2007 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2199 • Rev. 12/2007