

DRY FILM PTFE LUBRICANT



The dry film PTFE lubricant which minimizes friction and extends equipment life.

- Provides excellent lubrication
- Ideal for releasing molded parts
- Excellent for high temperature applications up to 500°F (260°C)
- Dry, thin film will not attract dust or dirt
- Nonflammable
- Does not contain silicone or chlorinated solvents
- Safe on most surfaces
- Meets USDA requirements for H2

Dry Film PTFE Lubricant is available in this size:

12 oz. (340 grams) aerosol Part No. 02616

Typical applications where Dry Film PTFE Lubricant can be used:

- Chutes & Slides
- Conveyor Belts
- Injection Molding
- Locks & Catches
- Metal Extrusions
- Silicone Rubber
- Tanks & Bins
- Thermoplastics
- Thermosets
- Window Guides

General Information

Dry Film PTFE Lubricant is excellent for applications involving rubber, plastic or metal. Because it can be used on many surfaces and at high temperatures, Dry Film PTFE Lubricant is a versatile lubricant and mold release agent. The dry film will not attract dust or dirt. Dry Film PTFE Lubricant does not contain silicone or chlorinated solvents.

Material Safety Data Sheets are available upon request.

Properties

Active Ingredient:
PTFE

Propellant:
Oxygenated Hydrocarbon/HFC

Flammability:
Nonflammable

Properties of Non-Volatiles

Color/Form:
White Solid

Temperature Range:
-40°F to 500°F



LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.

TEL: (800) 241-8334 or (770) 934-7800 • FAX: (800) 543-1563 or (770) 493-9206

Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2001 LPS Laboratories • All Rights Reserved • Rev. 09/2001 • Form #X2135-5