

FOOD GRADE SILICONE LUBRICANT



The dry film, food grade silicone lubricant for rubber, plastic and metal parts.

- Meets USDA requirements for H1
- Meets FDA Regulation 21 CFR 178.3570 for Incidental Food Contact
- Provides excellent lubrication
- Great for food processing and food handling applications
- Ideal for releasing molded parts
- Dry film will not attract dust or dirt
- Excellent for high temperature applications up to 500°F
- Does not contain chlorinated solvents

Food Grade Silicone Lubricant is available in this size:

10 oz. (284 grams) aerosol Part No. 01716

Typical applications where Food Grade Silicone Lubricant can be used:

- Belts
- Blow Molders
- Bottling Machines
- Compression Molders
- Conveyors
- Food Racks
- Injection Molders
- Rubber Mountings
- Plastic Gears

General Information

Food Grade Silicone Lubricant is ideal for applications involving rubber, plastic, and metal parts. It has a dry film which will not attract dust or dirt, and it is ideal for food processing and food handling applications. Food Grade Silicone Lubricant meets the USDA requirements for H1 and the FDA requirements for incidental food contact. Food Grade Silicone Lubricant is also ideal for releasing molded parts, and for applications in high temperature environments. Food Grade Silicone Lubricant is fast evaporating and does not contain chlorinated solvents.

Material Safety Data Sheets are available upon request

Properties

Active Ingredient:

Silicone

Propellant:

Hydrocarbon

Flammability:

Extremely Flammable

Properties of Non-Volatiles

Color/Form:

Clear, Colorless Liquid

Viscosity @ 77°F:

350cSt

Temperature Range:

-40°F to 500°F



LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.

TEL: (800) 241-8334 or (770) 934-7800 • FAX: (800) 543-1563 or (770) 493-9206

Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2001 LPS Laboratories • All Rights Reserved • Rev. 09/2001 • Form #X2135-6