



HEAVY-DUTY SILICONE

LUBRICANT



Conforms to:

21 CFR-178.3570 for Incidental Food Contact



Category Code HI
Registration No.:
059820 Aerosol
059821 Bulk

PACKAGES

Net Fill

13 oz. (369 grams) aerosol
5 gal. (18.93 liters)

Part No.

01516
01505

APPLICATIONS

- Belts
- Casters
- Chutes
- Conveyors
- Grinders
- Guards
- Guide Rails
- Mixers
- Molds
- Plastic Gears
- Rubber Bushings
- Rubber Mountings
- Slicers
- Slides
- Window Channels



PROPERTIES

Appearance/Physical State:

Milky white (liquid)
Clear film (dry)

Flash Point:

140°F (60°C) T.C.C. bulk fluid

% Non-volatiles:

5% minimum

Propellant:

Hydrocarbon

Specific Gravity:

0.93

Temperature Range (dried film)

-40°F (-40°C) to
500°F (260°C)

Viscosity at 77°F (25°C):

325 - 375cSt

VOC Content:

31% Aerosol
20% Bulk

FEATURES

- Silicone rich formula that lubricates and protects rubber, plastic and metal parts
- Water-based
- Safe on most surfaces
- Does not contain chlorinated solvents
- Provides excellent lubricity
- Ideal for surfaces like elastomers and plastics where petroleum based lubricants are unsuitable
- Eliminates sticking, binding, squeaking
- Dry, non-staining lubricant
- Colorless, odorless and non-toxic

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-0552 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2007 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2019 • Rev. 12/2007