

The high performance lubricant specially formulated for maximum lubricity and superior protection against wear and corrosion.

- Excellent for heavy load applications
- PTFE additives improve performance
- Extends equipment life
- Displaces moisture
- Protects against rust and corrosion
- Does not contain chlorinated solvents
- Safe to use on most surfaces
- Meets USDA requirements for H2

General Information

LPS Magnum Premium Lubricant with PTFE is a specially formulated lubricant which minimizes friction and extends equipment life. Magnum penetrates to displace moisture and protect against wear and corrosion.

Magnum contains a PTFE additive that minimizes surface-tosurface contact under extreme temperature and pressure conditions. The PTFE particles in Magnum coat and protect the working surface with a durable friction shield that is resistant to extreme load carrying situations.

Independent lab results have shown that Magnum out performs the leading competitors in the Shell 40/20 kg Four Ball Wear Test. Magnum prevented scarring 2 to 3 times better than the competition.

Material Safety Data Sheets are available upon request.

Magnum Premium Lubricant with PTFE is available in these sizes:

11 oz. (312 grams) aerosol 5 gal. (18.93 liters) Part No. 00616 00605

Typical applications where Magnum Premium Lubricant with PTFE can be used:

- Bearings and Valves
- Cables and Linkages
- Dies, Bits and Fasteners
- Engines and Electric Motors
- Hoists, Lifts and Draglines
- Metal Parts and Hand Tools
- Parts in Storage
 Production and
- Production and Transportation Equipment
- Pulleys and Rollers
- Slides and Tracks

Properties

Flash point: 175°F (79°C) TCC

Specific gravity: 0.863 @ 77°F

Propellant: Carbon dioxide

% Nonvolatile: 50%

