



## ALL-PURPOSE PENETRANT, LUBRICANT AND PROTECTANT



**Penetrates to loosen rusted or frozen parts. Lubricates and protects against corrosion and displaces moisture.**

- Displaces moisture
  - Provides a nondrying, long lasting, oily film
  - High flash point of 175°F (79°C)
  - Does not contain chlorinated solvents or silicones
  - Nonconductive
  - Safe on most surfaces
  - Meets NSF requirements for H2
- Registration #: 059842 (aerosol)  
059843 (bulk)
- Inverta Spray Valve lets you spray in an upright or inverted position

### Where can TKX be used?

#### Industrial

- Bearings
- Cables and Chains
- Castings
- Dies and Molds
- Forgings
- Gears
- Machined Stock
- Machinery
- Nuts and Bolts
- Pumps
- Pulleys
- Saw Blades
- Springs
- Stalled Engines
- Ways and Guides
- Wheels

#### General

- Doors
- Elevators
- Engines
- Fans
- Generators
- Keyways
- Locks
- Power/Hand Tools
- Valves
- Vises
- Window Frames

#### Electronic

- Circuit Boards
- Coils
- Electric Motors
- Gauges
- Ignition Systems
- Relays
- Switches
- Terminals

### General Information

TKX is an all-purpose penetrant, lubricant and protectant which will displace moisture, loosen frozen parts and protect against corrosion. TKX is an excellent lubricant for cables, gears, and chains. TKX provides a nondrying, oily film for lubricating equipment and machines. TKX has a high flash point of 175°F, so it can be used in areas where flammability may be a potential problem. TKX doesn't contain chlorinated solvents or silicones, and it is safe to use on most surfaces.

Material Safety Data Sheets are available upon request.

### Properties

#### Flash Point:

175°F (79°C) TCC

#### Specific Gravity:

0.845 @ 77°F

#### Pour Point:

-35°F (-37°C)

#### % Non-volatiles:

28 - 30%

#### Dielectric Strength and Breakdown Voltage (ASTM D-877):

>30,000 Volts

#### Propellant:

Carbon Dioxide

### TKX is available in these sizes:

11 ounce aerosol (312 grams)	02016
1 gallon (3.78 liters)	02028
5 gallons (18.93 liters)	02005
55 gallons (208 liters)	02055



**LPS Laboratories** • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.

TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)

©2006 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • All Rights Reserved • Rev. 3/2006 • Form #X2115