



GOLD GALVANIZE

CORROSION INHIBITOR



Conforms to: Mil-P-21035
ASTMA-780-93A

FEATURES

- >99% pure, zinc-rich, galvanize coating
- Performs like a hot dip galvanize to prevent rust and corrosion on all types of metals for up to three years
- Provides a tough, flexible coating that will not crack or peel even in extreme heat or cold
- Dries in 3-5 minutes
- Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C).
- Works as a paint primer over rust

PACKAGES

Net Fill

14 oz. (397 grams) aerosol
1 gal. (3.78 liters)

Part No.

00516
05128

APPLICATIONS

- Air Conditioning Parts
- Chain Link Fences
- Ducts
- Heating Parts
- Machine Housing
- Material Handling Equipment
- Newly Welded Surfaces
- Outside Storage Tanks
- Pipes
- Plumbing
- Pulley & Chain Cover
- Structural Steel



PROPERTIES

Appearance/Physical State:

Opaque Liquid

Boiling/Condensation Point:

281°F (138°C)

Color:

Gray

Odor:

Solvent

Flammable Limits (estimated):

LEL: 1.2%; UEL: 7.0%

Flash Point:

80°F (26°C) TCC (concentrate)

Temperature Range:

-30°F – 750°F (-34°C – 399°C)

Specific Gravity (water=1):

2.10

Vapor Density (air=1):

>2

VOC:

29.3% aerosol; 21% bulk

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2007 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2018 • Rev. 12/2007