

MICRO-X

FAST EVAPORATING CONTACT CLEANER



Ideal for removing dirt and oil from delicate electrical and electronic parts.

- Fast evaporation
- Quick penetration
- No residue
- Low odor
- Does not contain HCFC's
- Safe on metal and most plastics
- No rinsing
- Inverta Spray Valve allows one to spray in an upright or inverted position

Micro-X is available in these sizes:

11 oz. (312 grams) aerosol Part No. 04516
55 gal. (208 liters) 04555

General Information

Micro-X is ideal for removing dirt and oil from delicate electrical and electronic parts. Micro-X does not contain HCFC 141b and it is safe on metals and plastics. Micro-X is fast evaporating and will not leave a residue. Micro-X is ideal for applications where lower flash point contact cleaners can be used. Micro-X is flammable, so it should not be used on equipment in operation.

Material Safety Data Sheets are available upon request.

Properties

Flash point:
-20°F TCC

Surface tension:
17.3 dynes/cm @ 77°F

% Non-volatiles:
100 ppm maximum

Propellant:
Carbon Dioxide

KB value:
29

Dielectric strength and breakdown voltage (ASTM D-877):
30 kv

Specific gravity:
0.659 @ 77°F

% CFCs:
0

Typical applications where Micro-X can be used:

- Circuit Breakers
- Connectors
- Contacts
- Controls
- Fluid Systems
- Generators
- Instrumentation
- Keyboards
- Magnetic Tape Heads
- Motors
- Office Equipment
- Printed Circuits
- Relays
- Semiconductor Assemblies
- Sensors
- Switch Gears
- Switches
- Telecommunication Equipment
- Telephone Equipment
- Terminals
- TV Tuners
- Typewriters



LPS Laboratories • An Illinois Tool Works Company
P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.
TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899
Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2005 LPS Laboratories • All Rights Reserved • Rev. 3/2005 • Form #X4516