

TAPMATIC® *Dual Action* PLUS #2 Cutting Fluid



The cutting fluid made especially for machining aluminum.

- Provides superior lubricity in machining aluminum and its alloys
- Reduces friction
- Eliminates chip welding
- Improves surface finish
- Extends tool life

Typical applications where Tapmatic Dual Action Plus #2 Cutting Fluid can be used:

- Bending
- Boring
- Drilling
- Engraving
- Facing
- Forming
- Grinding
- Milling
- Reaming
- Sawing
- Tapping
- Threading
- Turning

Tapmatic Dual Action Plus #2 Cutting Fluid is available in these sizes:

Size	Part No.
16 fluid ounces (0.473)	40220
1 gallon (3.78 liters)	40230
5 gallons (18.93 liters)	40240
55 gallons (208 liters)	40260

General Information

Dual Action Plus #2 Cutting Fluid is designed especially for aluminum. Dual Action Plus #2 Cutting Fluid increases tool life and production, reduces costs, prevents tool seizure and galling, and assures a finer finish. It is safe for tapping, drilling, reaming, threading or finishing on aluminum.

Material Safety Data Sheets are available upon request.

Properties

Flash Point:

175°F

Color:

Light Yellow

Odor:

Mild Fatty

Specific Gravity:

.825



LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.

TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2004 LPS Laboratories • All Rights Reserved • Rev. 11/2004 • Form #X40220