

# DATA SHEET

## Wrightlease 2

### Extruded Fluoropolymer Pressure Sensitive Tape

#### ■ DESCRIPTION

Wrightlease 2 is an extruded Fluoropolymer film coated with silicone pressure sensitive adhesive. The yellow color is highly visible on most substrates in addition to offering high elongation and tensile strength.

##### Benefits:

- > Provides excellent release from all common resin systems for multiple releases.
- > Good adhesion to metal, composite, tooling block and rubber tooling.
- > High elongation allows for easier covering of complex contour surfaces.

#### ■ TECHNICAL DATA

Maximum use temperature	260 °C
Carrier type	Extruded Fluoropolymer
Adhesive type	Silicone
Colour	Light Yellow
Total thickness	90 µm
Film thickness	50 µm
Adhesive thickness	38 µm
Adhesion	Medium
Elongation at break	350 %
Shelf life	12 months
Storage conditions	22 °C

#### ■ SIZES

Width	Length	Packaging
1 inch (2,54 cm)	36 yards (33 m)	36 rolls per case
2 inches (5,08 cm)	36 yards (33 m)	18 rolls per case

#### ■ NOTES

- > Maximum use temperature is dependent upon duration at maximum temperature and is process specific.
- > Other sizes available on special order.