

LPS[®] LVC

CONTACT CLEANER



FEATURES

- Reduced VOCs (Volatile Organic Compounds)
- Conforms to CARB (California Air Resources Board) requirements for VOC emissions
- Fast evaporating
- Ideal for electrical/electronic and fine parts
- Cleans and degreases delicate precision mechanisms
- Safe on plastics
- Penetrating action removes oil, grease, dirt, flux and other contaminants
- Does not contain chlorinated solvents
- No residue

APPLICATIONS

- Connectors
- Contacts
- Fluid Systems
- Magnetic Tape Heads
- Office Equipment
- Printed Circuits
- Relays and Controls
- Semiconductor Assemblies
- Switches
- Telephone Equipment



PROPERTIES

% Non-Volatiles:
50 ppm maximum

VOC Content:
74%, 600 g/L

% HCFCs:
0%

KB Value:
23

Flash Point:
0°F (-18°C)

Specific Gravity (water=1):
0.811

Surface Tension:
17.3 dynes/cm @
77°F (25°C)

Propellant:
HFC - 134a

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

PACKAGE

Net Fill
11 oz. (312 grams) aerosol

Part No.
05416

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2007 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2229 • Rev. 11/2007